

## Wall Plugin Power Supply SN1-24

[www.kem.nt-rt.ru](http://www.kem.nt-rt.ru)

### Description

The power supply SN1-24 is designed to operate units requiring a 24V DC supply with 6W maximum power from the mains.

The SN1-24 is for indoor use only.

### Mounting and Connecting

#### Note:

Ever disconnect the SN1-24 from the mains before you make changes on the 24V installation!

Connect the red cable to the terminal "+24V" (with KEM FA\*, TCE\* and KCE\* terminal 50) and the white cable to terminal "-24V" or "24V GND" (with KEM FA\*, TCE\* and KCE\* terminal 51). For the correct procedure refer to the unit's manual.

Put the SN1-24 into the wall socket.



### Technical Data

|                  |                          |
|------------------|--------------------------|
| Protection Class | II                       |
| <b>Primary</b>   |                          |
| Supply voltage   | 100 – 240V AC $\pm 10\%$ |
| Frequency        | 47 – 63 Hz               |
| Connector        | Euro Connector           |
| <b>Secondary</b> |                          |
| Voltage          | 24V $\pm 3\%$            |
| Current          | 250 mA max.              |
| Power            | 6W max.                  |
|                  | short circuit proof      |

### Ordering Information

IPS7-9 Steckernetzteil 24V / 6W